

GAMA 94

Uw	0.79 W/m ² *K**
Rw	35 dB**
Pane	2-3 glass unit
Warranty	5 years.*

Window profile characteristics:

- Sliding doors
- Arched windows
- Doors
- Thermal profile

Especially warm

These windows have the thickest wooden frame profile. Best kind of protection from undesired environmental impact and best heat conservation.

We can also provide arched windows as well as exterior and sliding doors of similar designs. Horizontal surfaces covered in aluminium profile ducts are mounted for external protection against water and sunlight. Glass Unit Size: up to 56mm.

MATERIAL USED

Types of wood:	tenon pine, non-tenon pine, meranti, larch, oak, etc.
Painting:	Teknos/Finland/
Aluminium profiles:	Gutmann/Germany/
Furniture:	Roto/Germany/ G. U./Germany/
Glasses:	Saint-Gobain/France/
Gaskets:	Schlegel Q-Lon/Germany/
Handles:	Hoppe Atlanta/Germany/



* The warranty for window outdoor topping is provided subject to the type of wood and painting.

** Uw and Rw calculated for a window:

Measurements: height 1480 mm, width 1230 mm. Type of opening: internal opening, right. Bindings: ROTO. Fastening: 7 fixing points in perimeter. Gaskets: SCHLEGEL foam. Sealing sets: 2. Pane: glass unit, 4-14Ar-4-14Ar-4 (two glasses covered with low-e coating, openings filled with argon gas, spacers - Swispace Ultimate).