

# GAMA 78

|                 |                            |
|-----------------|----------------------------|
| <b>Uw</b>       | 0.88 W/m <sup>2</sup> *K** |
| <b>Rw</b>       | 35 dB**                    |
| <b>Pane</b>     | 2-3 glass unit             |
| <b>Warranty</b> | 5 years.*                  |

#### Window profile characteristics:

- Economy option
- Sliding doors
- Doors
- Arched windows

## Price leader

Traditional European windows. Among the most popular solutions in Lithuania due to their economic nature.

It is also possible to order arched windows as well as exterior and sliding doors of analogous designs. Horizontal surfaces covered in aluminium profile ducts are mounted for external protection against water and sunlight. Glass Unit Size: up to 42mm.

#### MATERIAL USED

|                            |   |
|----------------------------|---|
| <b>Types of wood:</b>      | tenon pine, non-tenon pine, meranti, larch, oak, etc. |
| <b>Painting:</b>           | Teknos/Finland/                                       |
| <b>Aluminium profiles:</b> | Gutmann/Germany/                                      |
| <b>Furniture:</b>          | Roto/Germany/<br>G. U./Germany/                       |
| <b>Glasses:</b>            | Saint-Gobain/France/                                  |
| <b>Gaskets:</b>            | Schlegel Q-Lon/Germany/                               |
| <b>Handles:</b>            | Hoppe Atlanta/Germany/                                |



\* The warranty for window outdoor topping is provided subject to the type of wood and painting.

\*\* Uw and Rw calculated for a window:

Measurements: height 1480 mm, width 1230 mm. Type of opening: internal opening, right. Bindings: ROTO. Fastening: 7 fixing points in perimeter. Gaskets: SCHLEGEL foam. Sealing sets: 2. Pane: glass unit, 4-14Ar-4-14Ar-4 (two glasses covered with low-e coating, openings filled with